

Dynaswivel® Air Line Connectors

Never Fight an Air Hose Again! For Use with Most Air Tools

THE PROBLEM



DYNABRADE

THE SOLUTION



- The Dynaswivel® is a "universal-joint" that connects portable air tools to an air line.
- It improves tool maneuverability, minimizes operator fatigue and extends hose life.
- Patented; works great on air tools or paint guns.

Aluminum and Stainless Steel Construction

Single Pivot

- Right angle "single-pivot" swivels 360° at one location.
- Designed to permit air hose to extend horizontally away from tool while allowing 360° tool maneuverability.
- Great for stationary equipment.



Part Number	Thread Size	Flow Control	Air Flow Range SCFM (LPM)	Weight lb. (kg)
95590**	1/4" NPT	No	up to 25 (708)	0.11 (0.05)
95591**	3/8" NPT	No	26-45 (736-1275)	0.26 (0.12)
95592**	1/2" NPT	No	46-65 (1303-1841)	0.46 (0.21)

Aluminum and Stainless Steel Construction

Double Pivot

- Swivels 360° AT TWO PIVOT POINTS allowing the air hose to drop directly to the floor while providing superb tool handling.



Double Pivot, Flow Control

- Swivels 360° AT TWO PIVOT POINTS allowing the air hose to drop directly to the floor while providing superb tool handling.
- Finger-tip air-flow control dial.



Part Number	Thread Size	Flow Control	Air Flow Range SCFM (LPM)	Weight lb. (kg)
95852**	1/8" Male x 25 1/4" NPT Female	No	up to 25 (708)	0.18 (0.08)
95460**	1/4" NPT	No	up to 25 (708)	0.20 (0.09)
95734**	1/4" NPT	Yes	up to 25 (708)	0.24 (0.11)
95461**	3/8" NPT	No	26-45 (736-1275)	0.40 (0.18)
95462**	1/2" NPT	No	46-65 (1303-1841)	0.80 (0.36)
95690**	3/4" NPT	No	above 65 (1840)	1.50 (0.68)

Non-Marring Composite Construction

Double Pivot

- Swivels 360° AT TWO PIVOT POINTS allowing the air hose to drop directly to the floor while providing superb tool handling.



Double Pivot, Flow Control

- Swivels 360° AT TWO PIVOT POINTS allowing the air hose to drop directly to the floor while providing superb tool handling.
- Finger-tip air-flow control dial.



Part Number	Thread Size	Flow Control	Air Flow Range SCFM (LPM)	Weight oz. (kg)
94300*	1/4" NPT	No	up to 33 (935)	2.15 (0.06)
94407*	1/4" NPT	Yes	up to 46 (1303)	2.40 (0.08)

96177 Dynaswivel® Display Pak

- Includes one counter top display box and ten 94300 Dynaswivel® Air Line Fittings.



IMPORTANT: 150 PSIG (10.3 Bar) maximum on all models

***NOTE:** Do not exceed recommended torque value of 28-30 newton meters

****NOTE:** Do not use on percussion tools or in areas of high mechanical abuse