

ExacTorq® Series Precision-Adjustable Torque Screwdrivers

Exact Torque Adjustment Using DigiLock Control Mechanism

Gone are the days of estimating torque. A simple twist of ExacTorq's end-mounted DigiLock mechanism sets your torque levels in exact, single digit increments. The positive locking detent secures your selection.

Enhanced Comfort and Accuracy with Advanced Ergonomics

Enhanced comfort translates into enhanced accuracy. The ExacTorq features a tri-lobular handle design. This gives users enhanced leverage, plus rounded surfaces for comfort and striated edges for superior grip control. With each turn, this unique design involves only major muscle groups to reduce strain and potential repetitive-motion injury. Additionally, the ExacTorq is comfortable in event the smallest of hands, performing flawlessly when used by women and men on the assembly line.

Shipped with Proof of Performance

Each ExacTorq is shipped with a certificate of calibration from our ISO/IEC 17025 Accredited Calibration Laboratory.

Features

- **DigiLock Control Mechanism revolutionizes manual torque adjustment.**
- **Positive locking detent secures selected torque value.**
- **Tri-lobular design gives users enhanced leverage, plus rounded surfaces for comfort and striated edges for superior grip control.**
- **Comfortable for all hand sizes.**
- **Can be used in both right and left hand directions.**
- **Meets or exceeds ASME B107.14M and ISO 6789 specifications.**
- **Precision tool - perfect for assembly operations where accurate torque values are required.**
- **To operate, simply dial torque and insert bit.**
- **Operator cannot over torque. Clutch releases automatically when desired torque has been achieved.**
- **Uses standard bits, sockets and adapters.**
- **Anti-backlash design enhances repeatability.**



[How does ExacTorq work?](#)
[Click here.](#)

Part No.	810045	810046
Capacity	20-100 in. oz.	15-74 cNm
Graduation	1 in. oz.	1cNm
Length (less bit)	6.75 in./172mm	6.75 in./172mm
Weight	6 oz . /.17kg	6 oz . /.17kg
Drive Size	.25 in. Female Hex	.25 in. Female Hex