


## FIJA ABIERTA CON CARRACA (ROE)

Línea de centro común de 1-7/16" (3,6 cm)

Una ligera desconexión con el tornillo o tuerca permite que el operador pueda girar la llave rápidamente



NÚMERO PIEZA	MODELO	TAMAÑO HEXÁGONO	APIRIETE MÁXIMO (Nm)	DIMENSION (mm)				
				A	B	C	D	E
• 819217	ROE-7mm	7 mm	7	42	19	5	13	14,3
• 819218	ROE-8mm	8 mm	10	42	19	5	13	14,3
• 819219	ROE-9mm	9 mm	13	43	27	6	19	17,5
• 819220	ROE-10mm	10 mm	13	43	27	6	19	17,5
• 819221	ROE-11mm	11 mm	20	43	27	6	19	17,5
• 819222	ROE-12mm	12 mm	23	46	34	8	19	17,5
• 819223	ROE-13mm	13 mm	23	46	34	8	19	17,5
• 819224	ROE-14mm	14 mm	27	46	34	8	19	17,5
• 819225	ROE-15mm	15 mm	40	46	41	9	22	17,5
• 819226	ROE-16mm	16 mm	40	46	41	9	22	17,5
• 819227	ROE-17mm	17 mm	54	46	41	9	22	17,5
• 819228	ROE-18mm	18 mm	54	46	41	9	22	17,5
• 819229	ROE-19mm	19 mm	68	49	47	10	26	21
• 819230	ROE-21mm	21 mm	85	49	47	10	26	21
• 819231	ROE-22mm	22 mm	101	50	54	11	32	21
• 819232	ROE-24mm	24 mm	118	50	54	11	32	21
• 819233	ROE-27mm	27 mm	152	53	59	12	32	21
• 819236	ROE-30mm	30 mm	186	58	70	13	32	21
• 819238	ROE-32mm	32 mm	203	58	70	13	32	21